1-800-985-5823

AMSOIL Material Safety Data Sheet

Section 1: Product and Company Identification

Manufacturer:	AMSOIL, Inc.
	925 Tower Avenue
	Superior, WI 54880

Telephone: CHEMTREC (Spill Emergency Only): 1-800-424-9300 Information: 715-392-7101

AMSOIL Product Code	APF
Product Label Name	Power Foam
Product Use Primarily Organic Based Surfactant C	leaning Solution

Section 2: Composition/Information on Ingredients

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)

			\sim	
Component	Cas#	Vapor Pr mm Hg @		Weight %
Aromatic petroleum distillate OSHA PEL: Not established, ACGIH TLV: Not established	64742-94-5	.5	68	25
Aromatic hydrocarbon OSHA PEL: Not established, ACGIH TLV: Not established	64742-94-5	.09	68	18
Hydrotreated light napthentic distillate OSHA PEL: 5 mg/m ³ (oil mist)	64742-53-6	.01	68	12
2-Butoxyethanol, glycol ether EB OSHA PEL: 25 ppm , ACGIH TLV: 25 ppm: Skin	111-76-2	.6	68	10
Morpholine OSHA PEL: 20 ppm , ACGIH TLV: 20 ppm: Skin	110-91-8	7	68	3
Propane OSHA PEL: 1000 ppm, ACGIH TLV: Asphyxiant	74-98-6	6350	68	8

Section 3: Hazards Identification

WARNING! Contents Under Pressure, Extremely Flammable, Vapor may cause flash fire POTENTIAL HEALTH EFFECTS: Eye, inhalation and skin irritant.

Section 4: First Aid Measures

- EYE: Do not rub eyes. Flush with large amounts volumes for 15-20 minutes. Seek medical attention.
- SKIN: Wash immediately with soap and water. Remove contaminated clothing and launder before reuse. Discard shoes and leather articles saturated with the product. Obtain medical advice if irritation occurs.
- INHALATION: Remove exposed person to fresh air. If breathing is labored give oxygen. If breathing has stopped apply artificial respiration. Get immediate medical attention.

INGESTION: DO NOT INDUCE VOMITING. If conscious, give 2 glasses of water. If vomiting does occur, keep head below hips to reduce risk of aspiration. Get immediate medical attention.

Section 5: Fire Fighting Measures

FLAMMABILITY PROPERTIES:	Flash Point	
	Method	Estimated
	LFL/UFL	
	Auto-ignition Temperature	Not Determined

Only): 1-800-424-9300 NFPA & HMIS Rating

Red Flammability

White

Special

N/A

Yellow

Instability

0

Blue

Health

2

Date Issued/Revised: June 17, 2008 Supersedes: November 15, 2004

AMSOIL Material Safety Data Sheet

EXTINGUISHING MEDIA: Foam, alchohol foam, CO2, dry chemical, water fog

UNUSUAL FIRE & EXPLOSION HAZARDS: Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharged contents. Vapor accumulation can flash or explode if ignited. Over exposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention

FIREFIGHTING EQUIPMENT: Full bunker gear recommended. Including a positive pressure self-contained breathing apparatus.

Section 6: Accidental Release Measures

Isolate spill area. Provide adequate ventilation. Wear appropriate personal protection. Recover free product for recycle and/or disposal. Add sand, earth or other suitable absorbent to spill area. Prevent entry into sewers and waterways. Check under Transportation and Labeling (DOT/CERCLA) and Other Regulator Information Section (SARA) for hazardous substances to determine regulatory reporting requirements for spill.

Section 7: Handling and Storage

- HANDLING: Do not puncture or incinerate can. Avoid contact with eyes, skin or clothing. Wash hands after handling. Empty container may retain product residue, which may exhibit hazards of product.
- STORAGE: Store and use in cool, dry, well-ventilated areas. Do not store above 120°F. Keep away from heat or flame.

Section 8: Exposure Controls/Personal Protection

VENTILATION: Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY: Use a NIOSH approved respirator when necessary.

SKIN: Use Viton or Nitrile gloves to avoid prolonged or repeated skin contact.

EYE: Use splash goggles or face shield where splashing is expected or can occur.

EXPOSURE LIMITS: The Threshold Limit Value (TLV) of 5 mg/m³ is suggested for oil mist.

Section 9: Physical and Chemical Properties

Physical State Boiling Point Freezing/Melting Point Vapor Pressure Vapor Density (Air=1) Evaporation Rate Solubility in Water Specific Gravity (Water=1)	
Density, lb./gal Volatility (Volume)	Unknown
VOC	Unknown
рН	Not Determined
Coefficient of Water/Oil Distribution	Not Determined
OdorSimilar to antifu	
Odor Threshold	
Appearance Transparent clear to milky cold	• • •
Viscosity, cSt @ 100°C	Not Applicable

Viscosity, cSt @ 40°C.....Not Applicable Viscosity Index.....Not Applicable

Section 10: Stability and Reactivity

STABILITY: Stable. Avoid applications to hot surfaces.

INCOMPATIBILITY: Avoid contact with strong oxidants.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION OF PRODUCT: May produce fumes when heated to decomposition. Toxic oxides of carbon.

Section 11: Toxicological Information

ACUTE EXPOSURE Eye Irritation:	Moderate to strong eye irritation. Based on data from components or similar material.
Skin Irritation:	Not expected to be a primary skin irritant. Based on data from components or similar material. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, defatting, and cracking of the skin.
Respiratory Irritation:	If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract similar to that observed with mineral oil. Based on data from components or similar materials. Under good industrial hygiene practices where all exposure limits are observed, respiratory irritation should not be a problem.
CHRONIC EXPOSURE	
Chronic Toxicity:	Some components may aggravate liver and kidney disease, anemia, coronary disease or rhythm disorders of the heart. Only in quantities exceeding the TLV
Carcinogenicity:	No data available to indicate product present at greater than 0.1% are a carcinogenic hazard.
Mutagenicity:	No data available to indicate product present at greater than 1.0% present a mutagenic or genotoxic hazard.
Reproductive Toxicity:	No data available to indicate product present at greater than 1.0% present a reproductive hazard.
Teratogenicity:	No data available to indicate product present at greater than 1.0% present a teratogenic hazards.

ADDITIONAL INFORMATION

Exposure Limits: Under conditions, which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.

There are extensive toxicological data available on the various components of this product. An adequate representation of all these data is beyond the scope of this document. Please contact the AMSOIL Material Safety Data Sheet Coordinator for more details.

Section 12: Ecological Information

No data available on the adverse effects of this product on the environment.

Section 13: Disposal Considerations

Material is expected to be hazardous when disposed. Dispose of in accordance with all local, state and federal regulations.

Section 14: Transport Information

This product is classified as Combustible liquids N.O.S., NA1993 for DOT shipping. Hazard Label ORM-D. For further information relative to spills resulting from transportation incidents, refer to the latest DOT Emergency Response Guidebook for Hazardous Materials.

Section 15: Regulatory Information

U.S. Federal Regulations

OSHA Table Z TSCA	Not Applicable
CERCLA 40 CFR 302.4	
SARA Title III Section 302 Extremely Hazardous	Not Applicable
Section 311/312 Fire Hazard	
Fire Hazard Reactive Hazard	
Release of Pressure Acute Health Hazard	
Chronic Health Hazard	
Section 313 Toxic Chemical 2-Butoxyethan	

U.S. State Regulations

California (Prop 65)

Does not contain chemicals known to the state of California to cause cancer.

International Regulations

WHMIS All components listed

Section 16: Other Information

The information and recommendations contained herein are, to the best of AMSOIL's knowledge and belief, accurate and reliable as of the date issued. AMSOIL makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and AMSOIL shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with AMSOIL's interpretation of the available data.