



The First in Synthetics®

Premium API CJ-4 15W-40 Synthetic Diesel Oil

Superior Shear Stability and Extended Drain Intervals in Ultra-Low Emission Diesel Engines

AMSOIL 15W-40 Synthetic Diesel Oil is the premium choice for API CJ-4 emission-quality diesel oil required by model-year 2007 and newer diesel engines. It delivers extraordinary lubrication in diesel engines found in commercial, fleet and personal vehicles. Formulated with the latest additive and synthetic base oil technology, AMSOIL Premium 15W-40 Synthetic Diesel Oil exceeds the higher performance demands of modern engines. It withstands the stress of heat, soot and acids to help prevent deposits, corrosion and wear.

AMSOIL, the leader in automotive synthetic lubrication, produced the world's first API-qualified synthetic motor oil in 1972. Trust the extensive experience of AMSOIL, *The First in Synthetics®*, to do the best job protecting your engine.



Meets Emission System Requirements

AMSOIL 15W-40 Synthetic Diesel Oil is a low-sulfated ash formulation that meets the requirements for low-emission quality diesel oil and protects under the most severe conditions found in modern diesel engines. It is compatible with all exhaust treatment devices and is designed for engines equipped with diesel particulate filters (DPF).

Extended Drain Performance

AMSOIL Premium 15W-40 Diesel Oil can extend drain intervals far beyond those recommended for conventional petroleum oils. Its unique synthetic formulation and long-drain additive system (10.4 TBN) deliver superior engine protection, cleanliness and performance over extended drain intervals. AMSOIL 15W-40 Synthetic Diesel Oil provides maximum protection for up to 3X the OEM-recommended drain interval, even further with oil analysis.

Controls Soot-Thickening and Wear

The advanced synthetic base oils in AMSOIL 15W-40 Diesel Oil are naturally resistant to soot contamination and oxidative thickening. That, along with a heavy fortification of detergent/dispersant additives, keeps soot particles suspended independently, helping prevent the formation of larger, wear-causing particles. Viscosity increase is minimized and soot-related wear is controlled.

Superior Shear Stability, Reduced Oil Consumption

AMSOIL 15W-40 Synthetic Diesel Oil has lower volatility (burn-off) than conventional petroleum oils, resulting in less oil vapor passing into the combustion chamber, lowering oil consumption and emissions. Lower volatility helps AMSOIL Premium Diesel Oil retain its viscosity after high-temperature service for continued depend-

TYPICAL TECHNICAL PROPERTIES

AMSOIL Premium API CJ-4 15W-40 Synthetic Diesel Oil (DME)

Kinematic Viscosity @ 100°C, cSt (ASTM D-445)	14.6
Kinematic Viscosity @ 40°C, cSt (ASTM D-445)	103.2
Viscosity Index (ASTM D-2270)	146
CCS Viscosity @ -20°C, cP (ASTM D-5293)	5184
Flash Point °C (°F) (ASTM D-92)	238 (460)
Fire Point °C (°F) (ASTM D-92)	254 (489)
Pour Point °C (°F) (ASTM D-97)	-40 (-40)
NOACK Volatility, % weight loss (g/100g) (ASTM D-5800)	6.8
Four-Ball Wear Test @ 40 kg, 75°C, 1200 rpm, 1 hr, Scar, mm (ASTM D-4172)	0.51
Total Base Number	10.4
High-Temperature/High-Shear Viscosity, cP (ASTM D-5481)	4.2
Sulfated Ash Content, wt. %	1.0

Ideal for Fleets

AMSOIL Premium 15W-40 Diesel Oil reduces operating costs through extended drain intervals. It is engineered for a wide range of applications, allowing fleet operators to consolidate engine oil inventories in mixed fleets. In addition, it reduces downtime through extended drain intervals and improved equipment protection.

AMSOIL 15W-40 Diesel Oil costs less per mile than conventional oil.

Fleet Savings vs. Conventional 15W-40	Total Lubricant Used	Cost Per Gallon	Total Lubricant Cost x1 Truck	Total Lubricant Cost x50 Trucks
Conventional 15W-40	8 gal X12=96 gal	\$15.61	\$1,499	\$74,950
AMSOIL Synthetic 15W-40	8 gal X4=32gal	\$37.35	\$1,195	\$59,750
TOTAL SAVINGS WITH AMSOIL			\$ 304	\$15,200

Based on 120,000 miles per year with an OEM-recommended drain interval of 10,000 miles. Does not include labor, filter, or used oil disposal costs, making AMSOIL even more cost-effective. Pricing samples are suggested retail, June 2011.

APPLICATIONS

AMSOIL Premium CJ-4 15W-40 Synthetic Diesel Oil is recommended for diesel engines and, where appropriate, gasoline engines requiring any of the following specifications:

- SAE 15W-40
- API CJ-4, CI-4+, CF, SM
- ACEA E7, E9
- Mack EO-O Premium Plus
- DDC Power Guard 93K218
- Caterpillar ECF-3, ECF-2
- Cummins 20081
- Volvo VDS-4
- MB 228.31
- MS10902
- MTU Type I & II
- MAN 3275
- JASO DH-2
- Global DHD-1
- Renault RLD-3

COMPATIBILITY

AMSOIL 15W-40 Synthetic Diesel Oil is compatible with conventional and synthetic motor oils. Mixing AMSOIL motor oils with other oils, however, will shorten the oil life expectancy and reduce the performance benefits. AMSOIL does not support extended drain intervals where oils have been mixed.

Aftermarket oil additives are not recommended for use with AMSOIL motor oils.

SERVICE LIFE

AMSOIL Premium CJ-4 15W-40 Synthetic Diesel Oil is recommended for extended drain intervals in engines that are unmodified and in good operating condition.

Diesel Engine Service

- Three times (3X) OEM* recommendation, not to exceed 50,000 miles/600 hours or one year, whichever comes first. Drain intervals may be extended further with oil analysis.
- 2007-2009 Caterpillar C13 and C15 on-highway engines must follow OEM-recommended drain interval.
- 2007-Present Dodge, Ford and GM light-duty diesel pickups must follow OEM-recommended drain interval. Drain intervals may be extended with oil analysis.

Gasoline Engine Service

- Two times (2X) OEM* recommendation, not to exceed 15,000 miles or one year, whichever comes first.

*Operating conditions and drain intervals for severe and normal service are defined by the OEM. Refer to your owner's manual.

Note: Extended drain intervals are not recommended when using bio-fuels containing >10% ethanol or 5% biodiesel (B5). Follow OEM drain intervals or extend drain intervals with oil analysis.

HEALTH & SAFETY

This product is not expected to cause health concerns when used for the intended application and according to the recommendations in the Material Safety Data Sheet (MSDS). An MSDS is available via the Internet at www.amsoil.com or upon request at (715) 392-7101. **Keep Out of Reach of Children.** Don't pollute. Return used oil to collection centers.

For AMSOIL warranty information, visit www.amsoil.com.



Contact your AMSOIL Dealer for more information on AMSOIL products or to place an order. You may also order direct by calling AMSOIL INC. at 1-800-956-5695 and providing the referral number listed here. ▼

Referral # _____