

Revision date: 8/28/2019



SAFETY DATA SHEET
Chain Lube

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200 and WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR).

1. Identification

Product identifier

Product name Chain Lube
Product number ACLSC, ACL4SC

Recommended use of the chemical and restrictions on use

Application Chain lubricant.
Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier AMSOIL INC.
14328-121A Ave
Edmonton, AB T5L 2T2
T: 877-830-4769

Manufacturer AMSOIL INC.
One AMSOIL Center,
Superior, WI 54880, USA.
T: +1 715-392-7101
compliance@amsoil.com

Emergency telephone number

Emergency telephone CHEMTREC: Within USA and Canada: 1-800-424-9300
Outside the USA and Canada: +1 703-741-5970
(collect calls accepted) 24/7

2. Hazard(s) identification

Classification of the substance or mixture

OSHA/WHMIS Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard and according to the hazard criteria of the Hazardous Product Regulations.
Physical hazards Flam. Aerosol 1 - H222 Press. Gas, Compressed - H280
Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304
Environmental hazards Aquatic Chronic 2 - H411

Label elements

Hazard symbols



Signal word Danger

Chain Lube

Hazard statements	H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use P260 Do not breathe spray. P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 If swallowed: Immediately call a poison center/ doctor. P302+P352 If on skin: Wash with plenty of water. P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing. P312 Call a poison center/ doctor if you feel unwell. P331 Do NOT induce vomiting. P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410+P403 Protect from sunlight. Store in a well-ventilated place. P412 Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with national regulations.
Contains	Hydrogenated base oil, Butene, homopolymer, Hydrogenated base oil

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Hydrogenated base oil CAS number: 64742-49-0	25 - <50%
Butane CAS number: 106-97-8	10 - <25%
Butene, homopolymer CAS number: 9003-29-6	10 - <25%
Propane CAS number: 74-98-6	5 - <10%

Chain Lube

Hydrogenated base oil	3 - <5%
CAS number: 8052-41-3	

Composition comments The exact percentage is withheld as a trade secret in accordance with 29 CFR 1910.1200.

4. First-aid measures

Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical attention if symptoms are severe or persist.
Skin Contact	Rinse with water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.
Ingestion	Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	Redness. Irritating to skin.
Eye contact	May be slightly irritating to eyes. May cause discomfort.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
----------------------	------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Chain Lube

Specific hazards	Containers can burst or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Vapors may form explosive mixtures with air.
Hazardous combustion products	Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO2).
Advice for firefighters	
Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Do not touch or walk into spilled material. Evacuate area. No smoking, sparks, flames or other sources of ignition near spillage. Risk of explosion. Provide adequate ventilation. Use protective equipment appropriate for surrounding materials. Promptly remove any clothing that becomes contaminated.
----------------------	--

Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground.
---------------------------	---

Methods and material for containment and cleaning up

Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Do not empty into drains. Absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. For waste disposal, see Section 13. Wash thoroughly after dealing with a spillage.
-------------------------	---

Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
-----------------------------	---

7. Handling and storage

Precautions for safe handling



Chain Lube

Usage precautions	Read and follow manufacturer's recommendations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid exposing aerosol containers to high temperatures or direct sunlight. Keep away from food, drink and animal feeding stuffs. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with eyes. Avoid inhalation of vapors and spray/mists. Do not handle broken packages without protective equipment. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with used product. Do not reuse empty containers.
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions	Store away from incompatible materials (see Section 10). Store locked up. Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F.
---------------------	---

Storage class	Miscellaneous hazardous material storage.
---------------	---

Specific end uses(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.
---------------------	---

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

Under conditions which may generate mists, the following exposure limits are recommended:
Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³
Short-term exposure limit (15-minute): ACGIH 10 mg/m³

Butane

Short-term exposure limit (15-minute): ACGIH 1000 ppm 2370 mg/m³

Propane

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 1800 mg/m³

Hydrogenated base oil

Long-term exposure limit (8-hour TWA): OSHA 500 ppm 2900 mg/m³
Long-term exposure limit (8-hour TWA): ACGIH 100 ppm 525 mg/m³
ACGIH = American Conference of Governmental Industrial Hygienists.
OSHA = Occupational Safety and Health Administration.

Ingredient comments	The constituents listed are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.
---------------------	---

Propane (CAS: 74-98-6)

Immediate danger to life and health	2100 ppm
-------------------------------------	----------

Hydrogenated base oil (CAS: 8052-41-3)

Chain Lube

Immediate danger to life and health 20,000 mg/m³

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

Respiratory protection

Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Aerosol. Liquid.
Color	Clear.
Odor	Solvent.
Odor threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	Not available.

Chain Lube

Evaporation rate	<1 (diethyl ether = 1)
Flammability (solid, gas)	Level 3 Aerosol.
Upper/lower flammability or explosive limits	Not available.
Vapor pressure	Not available.
Vapor density	> Air.
Relative density	Not available.
Solubility(ies)	Not known.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not applicable.
Explosive properties	Not considered to be explosive.
Oxidizing properties	Does not meet the criteria for classification as oxidizing.
Other information	No information required.

10. Stability and reactivity

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	The following materials may react strongly with the product: Oxidizing agents.
Conditions to avoid	Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised container: may burst if heated
Materials to avoid	Strong oxidizing agents.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

11. Toxicological information

<u>Information on toxicological effects</u>	
<u>Acute toxicity - oral</u>	
Summary	Based on available data the classification criteria are not met.
<u>Acute toxicity - dermal</u>	
Summary	Based on available data the classification criteria are not met.
<u>Acute toxicity - inhalation</u>	
Summary	Based on available data the classification criteria are not met.
<u>Skin corrosion/irritation</u>	
Summary	Causes skin irritation.

Chain Lube

Serious eye damage/irritation

Summary Based on available data the classification criteria are not met.

Respiratory sensitization

Summary Based on available data the classification criteria are not met.

Skin sensitization

Summary Based on available data the classification criteria are not met.

Germ cell mutagenicity

Summary Based on available data the classification criteria are not met.

Carcinogenicity

Summary Based on available data the classification criteria are not met.

IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

Summary Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Summary May cause drowsiness or dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

Summary May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Summary May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Skin Contact Redness. Irritating to skin.

Eye contact May be slightly irritating to eyes. May cause discomfort.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target Organs Central nervous system

12. Ecological information

Acute aquatic toxicity

Summary Based on available data the classification criteria are not met.

Chronic aquatic toxicity

Summary Toxic to aquatic life with long lasting effects.

Persistence and degradability



Chain Lube

Persistence and degradability	The degradability of the product is not known.
<u>Bioaccumulative potential</u>	
Bio-Accumulative Potential	No data available on bioaccumulation.
Partition coefficient	Not available.
<u>Mobility in soil</u>	
Mobility	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
<u>Other adverse effects</u>	
Other adverse effects	None known.

13. Disposal considerations

Waste treatment methods

General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Do not empty into drains. Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents.

14. Transport information

General	For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.
<u>UN Number</u>	
UN No. (TDG)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (DOT)	UN1950
<u>UN proper shipping name</u>	
Proper shipping name (TDG)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS (CONTAINS Hydrogenated base oil)
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (DOT)	AEROSOLS
<u>Transport hazard class(es)</u>	
DOT hazard class	2.1
DOT hazard label	2.1
TDG class	2.1

Chain Lube

TDG label(s)	2.1
IMDG Class	2.1
ICAO class/division	2.1

DOT transport labels



Transport labels



Packing group

TDG Packing Group	None
IMDG packing group	None
ICAO packing group	None
DOT packing group	None

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS	F-D, S-U
-----	----------

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15. Regulatory information

Regulatory References	OSHA Hazard Communication Standard 29 CFR §1910.1200 Hazardous Products Regulation (SOR/2015-17) Transportation of Dangerous Goods Regulations -SOR/2015-100.
-----------------------	---

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

Chain Lube

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

Propane

1.0 %

Paraffin waxes and Hydrocarbon waxes, chloro

0.1 %

CAA Accidental Release Prevention

The following ingredients are listed or exempt:

Propane

Threshold Quantity: 10000 lbs

FDA - Essential Chemical

None of the ingredients are listed or exempt.

FDA - Precursor Chemical

None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

Aspiration hazard
Gas under pressure
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

Hydrogenated base oil

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Propane

Hydrogenated base oil

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

Propane

Hydrogenated base oil

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

Propane

Chain Lube

Hydrogenated base oil

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

Propane

Hydrogenated base oil

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Propane

Hydrogenated base oil

Inventories

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

Abbreviations and acronyms used in the safety data sheet

TDG: The transport of dangerous goods act

IATA: International air transport association.
ICAO: Technical instructions for the safe transport of dangerous goods by air.
IMDG: International maritime dangerous goods.
CAS: Chemical abstracts service.
ATE: Acute toxicity estimate.
LC₅₀: Lethal concentration to 50 % of a test population.
LD₅₀: Lethal dose to 50% of a test population (median lethal dose).
EC₅₀: 50% of maximal effective concentration.
PBT: Persistent, bioaccumulative and toxic substance.
vPvB: Very persistent and very bioaccumulative.

Classification abbreviations and acronyms

Aerosol = Aerosol
Skin Irrit. = Skin irritation
STOT RE = Specific target organ toxicity-repeated exposure
STOT SE = Specific target organ toxicity-single exposure
Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Training advice

Only trained personnel should use this material.

Revision comments

This is the first issue.

Revision date

8/28/2019

SDS No.

8835

Hazard statements in full

H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Chain Lube

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.