



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA HCS 2024 and Canada Hazardous Products Act (HPA) and
Hazardous Products Regulation (HPR), as amended

Issuing Date 04-Aug-2025 Revision date 04-Aug-2025 Revision Number 1

1. Identification

Product identifier

Product Name AMSOIL Air Filter Oil

Other means of identification

Product Code(s) AFOSC

UN number or ID number UN1950

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Air filter oil

Restrictions on use Avoid formation of mists

Details of the supplier of the safety data sheet

Supplier Address
AMSOIL INC.
Bay Adelaide Centre, East Tower
22 Adelaide St. W
Toronto, ON, Canada M5H 4E3
T: +1 877-822-5172

Manufacturer Address
AMSOIL INC.
One AMSOIL Center
Superior, WI 54880, USA
T: +1 715-392-7101

E-mail compliance@amsoil.com

Emergency telephone number

Emergency telephone CHEMTREC: Within USA and Canada: 1-800-424-9300
Outside the USA and Canada: +1 703-741-5970
(collect calls accepted) 24/7

2. Hazard(s) identification

Classification of the substance or mixture

Aerosols	Category 1
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Category 3 Target organ effects: Narcotic effects.	
Aspiration hazard	Category 1

Label elements

Danger

Hazard statements

Extremely flammable aerosol.
Pressurized container: May burst if heated.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling.
Avoid breathing dust, fume, gas, mist, vapors and spray.
Use only outdoors or in a well-ventilated area.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not pierce or burn, even after use.
Do not spray on an open flame or other ignition source.
Wear protective gloves, protective clothing, eye protection and face protection.

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label).

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice and attention.

Skin

IF ON SKIN: Wash with plenty of water and soap.
If skin irritation occurs: Get medical advice and attention.
Take off contaminated clothing and wash it before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor if you feel unwell.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available.

Other information

May be harmful in contact with skin. May be harmful if inhaled.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%
Heptane, branched, cyclic and linear	426260-76-6	33-40
Polyolefin	9003-29-6	15-25
Base oil	64742-52-5	15-25
Propane	74-98-6	8-18
Butane	106-97-8	7-15
Base oil	64742-62-7	7-15
Base oil	64742-58-1	<1

Chemical Additions
The classification as a carcinogen does not apply as it can be shown that the Base oil(s) contain(s) less than 3% DMSO extract as measured by IP 346.

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	IF INHALED: Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.
Eye contact	IF IN EYES: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	IF ON SKIN: Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	None known.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.
--------------------	---



5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.
Hazardous combustion products	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.
Reference to other sections	For additional information see: Section 8: Exposure controls/personal protection; Section 12: Ecological information; Section 13: Disposal considerations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. In case of rupture: Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure.
-------------------------	---



Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control Parameters

Exposure Limits The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV		OSHA PEL	NIOSH
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard Sa		TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	TWA: 1000 ppm; TWA: 1800 mg/m³; IDLH: 2100 ppm
Butane 106-97-8	STEL: 1000 ppm explosion hazard		(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m³	TWA: 800 ppm; TWA: 1900 mg/m³; IDLH: 1600 ppm
Chemical name	Alberta	British Columbia	Ontario	Quebec
Propane 74-98-6	TWA: 1000 ppm;	Sa	: ; Sa (See Appendix F: Minimal Oxygen Content;explosion hazard)	Sa
Butane 106-97-8	TWA: 1000 ppm;	STEL: 1000 ppm;	: ; STEL: 1000 ppm;	TWAEV: 800 ppm; TWAEV: 1900 mg/m³;

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Propane	: ; Sa (See Appendix F: Minimal Oxygen Content)	: ;	: ;	: ; Sa (See Appendix F: Minimal Oxygen Content)
Butane	STEL: 1000 ppm;	STEL: 1000 ppm;	STEL: 1000 ppm;	STEL: 1000 ppm;

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Propane	TWA: 1000 ppm; STEL: 1250 ppm;	: ;	TWA: 1000 ppm; STEL: 1250 ppm;	Sa
Butane	TWA: 1000 ppm;	STEL: 1000 ppm;	TWA: 1000 ppm;	TWA: 600 ppm;



Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
	STEL: 1250 ppm;		STEL: 1250 ppm;	TWA: 1400 mg/m³; STEL: 750 ppm; STEL: 1600 mg/m³;

Note	See section 16 for terms and abbreviations.
Other information on limit values	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).
Biological occupational exposure limits	This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.
Appropriate engineering controls	
Engineering controls	Ensure adequate ventilation, especially in confined areas.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Hand protection	Wear suitable gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Antistatic boots. Chemical resistant apron. Wear fire/flame resistant/retardant clothing.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Use appropriate respiratory protection.
Environmental exposure controls	Avoid release to the environment.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

9. Physical and chemical properties

Information on basic physical and chemical properties	
Appearance	Aerosol
Physical state	Liquid
Color	Colorless
Odor (includes odor threshold)	Petroleum

Property	Values	Remarks • Method
Melting point / freezing point		No data available
Boiling point (or initial boiling point or boiling range)		No data available
Flammability		Extremely flammable aerosol
Flammability Limit in Air		
Upper flammability or explosive limits	9.5% v/v	No data available
Lower flammability or explosive limits	2.1%	No data available
Flash point	-104 °C / -155.2 °F	No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
SADT (°C)		No data available
pH		No data available
pH (as aqueous solution)		No data available
Kinematic viscosity		No data available



Dynamic viscosity		No data available
Solubility		No data available
Water solubility		No data available
Partition coefficient n-octanol/water (log value)		No data available
Vapor pressure (includes evaporation rate)	95 x 10^4	No data available
Evaporation rate		No data available
Density and/or relative density		No data available
Bulk density		No data available
Liquid Density		No data available
Relative vapor density	1.56	@ 0 °C (air = 1)
Particle characteristics		
Particle Size		No data available
Particle Size Distribution		No data available
<u>Other information</u>		
Molecular weight	No information available	
VOC content	24.97%	
Softening point	No information available	
<u>Information with regard to physical hazard classes</u>		
<u>Explosives</u>		
Explosive properties	No information available	
Oxidizing properties	No information available	

10. Stability and reactivity

Reactivity	None under normal use conditions.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

11. Toxicological information

Information on likely routes of exposure

Product Information	
Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness. May be harmful if inhaled.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Repeated exposure may cause skin dryness or cracking. Causes skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if



swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity Based on available data, the classification criteria are not met.

Numerical measures of toxicity

The following ATE values have been calculated for the mixture:

ATEmix (dermal) 3,603.60 mg/kg
ATEmix (inhalation-dust/mist) 8.72 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Polyolefin	-	> 2000 mg/kg (Rat)	> 19171 mg/m³ (Rat) 4 h
Base oil	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Propane	-	-	> 800000 ppm (Rat) 15 min
Butane	-	-	= 658 g/m³ (Rat) 4 h
Base oil	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2.18 mg/L (Rat) 4 h
Base oil	> 2000 mg/kg (Rat)	> 4480 mg/kg (Rabbit)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The classification as a carcinogen does not apply as it can be shown that the Base oil(s) contain(s) less than 3% DMSO extract as measured by IP 346.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Base oil 64742-52-5	A2 - Suspected human carcinogen	Group 1 - Carcinogenic to humans	Known human carcinogen	Present
Base oil 64742-62-7	A2 - Suspected human carcinogen	Group 1 - Carcinogenic to humans	Known human carcinogen	Present

Reproductive toxicity No information available.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure No information available.

Aspiration hazard May be fatal if swallowed and enters airways.



12. Ecological information

Ecotoxicity The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Polyolefin 9003-29-6	-	-	-	EC50: >100mg/L (48h, Daphnia magna)
Base oil 64742-52-5	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)
Base oil 64742-62-7	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Polyolefin 9003-29-6	7.8
Propane 74-98-6	1.09
Butane 106-97-8	2.31

Other adverse effects No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused products	Should not be released into the environment, Dispose of in accordance with local regulations, Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

14. Transport information

DOT

UN number or ID number	UN1950
Proper shipping name	Aerosols
Transport hazard class(es)	2.1
Special Provisions	N82
DOT Marine Pollutant	NP
Description	UN1950, Aerosols, 2.1
Emergency Response Guide Number	126

TDG

UN number or ID number	UN1950
Proper shipping name	Aerosols



Transport hazard class(es)	2.1
Description	UN1950, Aerosols, 2.1
IATA	
UN number or ID number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Environmental hazards	No
Special Provisions	A145, A167, A802
ERG Code	10L
Description	UN1950, Aerosols, flammable, 2.1
IMDG	
UN number or ID number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	2.1
Marine pollutant indicator	NP
Special Provisions	63,190, 277, 327, 344, 381, 959
EmS-No.	F-D S-U
Description	UN1950, Aerosols, 2.1, (-104°C c.c.)

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

- The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable
- The Stockholm Convention on Persistent Organic Pollutants Not applicable
- The Rotterdam Convention Not applicable

International Inventories

Contact supplier for inventory compliance status

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CAA (Clean Air Act)

This product does not contain any substances regulated as pollutants pursuant to Clean Air Act (CAA).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level



pertaining to releases of this material.

US State Regulations

California Proposition 65
This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Propane 74-98-6	X	X	X
Butane 106-97-8	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 2	Flammability 4	Instability 0	Special hazards -
HMIS	Health hazards 3	Flammability 4	Physical hazards 0	Personal protection X

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend	
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Europe)
ADR	Agreement concerning the International Carriage of Dangerous Goods by Road (Europe)
AIIC	Australian Inventory of Industrial Chemicals
ATE	Acute Toxicity Estimate
ASTM	American Society for the Testing of Materials
bar	Biological Reference Values for Chemical Compounds in the Work Area
BAT	Biological tolerance values for occupational exposure
BEL	Biological exposure limits
bw	Body weight
Ceiling	Maximum limit value
CMR	Carcinogen, Mutagen or Reproductive Toxicant
DOT	Department of Transportation (United States)
DSL	Domestic Substances List (Canada)
EmS	Emergency Schedule
ENCS	Existing and New Chemical Substances (Japan)
EPA	U.S. Environmental Protection Agency
GHS	Globally Harmonized System
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO	International Civil Aviation Organization
IECSC	Inventory of Existing Chemical Substances in China
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization



ISO	International Organization for Standardization
KECI	Korean Existing Chemicals Inventory
LC50	Lethal Concentration to 50% of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
MARPOL	International Convention for the Prevention of Pollution from Ships
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
n.o.s.	Not Otherwise Specified
NOAEC	No Observed Adverse Effect Concentration
NOAEL	No Observed Adverse Effect Level
NOELR	No Observable Effect Loading Rate
NTP	National Toxicology Program (United States)
NZIoC	New Zealand Inventory of Chemicals
OECD	Organization for Economic Cooperation and Development
OEL	Occupational exposure limits
OSHA	Occupational Safety and Health Administration of the US Department of Labor
PBT	Persistent, Bioaccumulative and Toxic substance
PICCS	Philippines Inventory of Chemicals and Chemical Substances
PMT	Persistent, Mobile and Toxic
PPE	Personal protective equipment
QSAR	Quantitative Structure Activity Relationship
RID	Agreement concerning the International Carriage of Dangerous Goods by Rail (Europe)
SADT	Self-Accelerating Decomposition Temperature
SAR	Structure-activity relationship
SARA	Superfund Amendments and Reauthorization Act
SDS	Safety Data Sheet
SL	Surface Limit
STEL	Short Term Exposure Limit
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
TCSI	Taiwan Chemical Substance Inventory
TDG	Transport of Dangerous Goods (Canada)
TSCA	Toxic Substances Control Act (United States)
TWA	Time-Weighted Average
UN	United Nations
VOC	Volatile organic compounds
vPvB	Very Persistent and Very Bioaccumulative
vPvM	Very Persistent and Very Mobile
As	Allergenic substance
DS	Dermal Sensitizer
Ot	Ototoxicant
pOt	Ototoxicant - potential to cause hearing disorders
PS	Photosensitizer
RS	Respiratory Sensitizer
S	Sensitizer
poS	Sensitizer - capable of causing occupational asthma
Sa	Simple asphyxiant
Sd	Skin designation
pSd	Skin designation - potential for cutaneous absorption
Sdv	Skin designation - vacated
Sk	Skin notation
dSk	Skin notation - danger of cutaneous absorption
pSk	Skin notation - potential for cutaneous absorption

Key literature references and sources for data used to compile the SDS

U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)



U.S. Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set
United Nations World Health Organization (WHO)

Issuing Date 04-Aug-2025
Revision date 04-Aug-2025
Revision Note Initial Release.

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

